

PDC Smart[®] Rewearable Wristbands



PDC Smart[®] Rewearable wristbands are made of 100% silicone with a securely sealed radio frequency identification (RFID) tag inside to reliably store and transfer data. Flexible, waterproof silicone material makes it comfortable and durable for long lasting use.

Serves as the perfect souvenir or to sell in your gift shop for retail revenue.

www.pdcsolutions.com

PDC Smart® Rewearable UHF RFID Wristbands

Superior read distance is ideal for timing events (such as marathons or competitions), passive tracking, and festivals.

- **Material:** Constructed of 100% silicone and embedded UHF transponder. Features a silicone strap to maximize artwork footprint.
- **Quantity:** 250 per box.
- **Packaging:** 11¹³/₁₆" L x 11" W x 11¹³/₁₆" H, 9.75 lbs.
- **Custom Options:** Choose from a combination of silk screen printing, debossing, and embossing. See custom specifications on next page. Please inquire for custom serialization and encoding options.
- **Lead Time:** Ships 3 weeks from date of artwork approval & payment terms.

PDC Smart® Rewearable RFID Wristbands

Ideal for use as a season pass, gym membership, or other premium credential.

- **Material:** Constructed of 100% silicone and embedded transponder.
- **Quantity:** 250 per box.
- **Packaging:** 10"L x 11 ⁵/₈"W x 10"H, 9.75 lbs.
- **Custom Options:** Choose from a combination of silk screen printing, debossing, and embossing. See custom specifications on next page.
- **Lead Time:** 3 weeks from date of artwork approval & payment terms.



Part Numbers:

| Options | UHF |
|----------|---------------|
| Adult 8" | RWUA-XX-PDJ-I |
| Youth 7" | RWUB-XX-PDJ-I |
| Child 6" | RWUC-XX-PDJ-I |

See RFID Tag specifications on back cover



Part Numbers:

| Options | ICODE-SLI | Tag-It Plus | Mifare 1K |
|----------|---------------|---------------|---------------|
| Adult 8" | RWSD-XX-PDJ-I | RWTD-XX-PDJ-I | RWMD-XX-PDJ-I |
| Youth 7" | RWSE-XX-PDJ-I | RWTE-XX-PDJ-I | RWME-XX-PDJ-I |
| Child 6" | RWSF-XX-PDJ-I | RWTF-XX-PDJ-I | RWMF-XX-PDJ-I |

See RFID Tag specifications on back cover

Substitute "XX" for colored number:


| | | | | |
|----------------------|------------------|--------------------|-------------------|----------------|
| WHITE 11 | LIGHT PINK 12 | BLUE 13 | YELLOW 14 | RED 16 |
| ORANGE 17 | LIGHT BLUE 18 | BLACK 20 | KELLY GREEN 22 | LAVENDER 23 |
| CRANBERRY 25 | GRAY 26 | HOT PINK 27 | GRAPE 33 | AQUA 35 |
| DAY GLOW GREEN 39 | GOLD 51 | FOREST GREEN 20 | TEAL 67 | KHAKI 99 |

Actual wristband colors may vary, especially day glow colors

Rewearable RFID Wristband Custom Specifications:

Boost your brand by customizing your PDC Smart® Rewearable wristbands with any combination of silk screen printing, debossing, and embossing.

- Silk Screen and Emboss/Deboss mold fees apply
- See artwork specifications on back cover



Silk Screen Printing

Print with up to 2 colors inside or outside strap. Standard silk screen colors are black & white. Contact customer service at 866.403.6526 ext.1556 for additional silk screen color options.

| Options | A | B |
|----------|----------------|---------------|
| Adult 8" | 1.2"L x 0.7" W | 1.6"L x 0.2"W |
| Youth 7" | 1.2"L x 0.7" W | 1.6"L x 0.1"W |
| Child 6" | 1.1"L x 0.6" W | 1.6"L x 0.1"W |



Debossing

Engraved lettering available inside or outside of strap. Deboss depth = 0.02"

| Options | A | B |
|----------|---------------|---------------|
| Adult 8" | 2.4"L x 0.1"W | 1.6"L x 0.2"W |
| Youth 7" | 1.8"L x 0.1"W | 1.2"L x 0.1"W |
| Child 6" | 1.6"L x 0.1"W | 1.2"L x 0.1"W |



Embossing

Raised lettering available with or without additional silk screen printing. Emboss height = 0.02"

| Options | A | B |
|----------|---------------|---------------|
| Adult 8" | 2.4"L x 0.1"W | 1.4"L x 0.2"W |
| Youth 7" | 1.8"L x 0.1"W | 1.0"L x 0.1"W |
| Child 6" | 1.6"L x 0.1"W | 1.0"L x 0.1"W |

PDC Smart® Rewearable Wristband Principal Applications:

- Social Media Integration
- Cashless Payments
- Access Control & Security
- Promotional, Customer Loyalty & VIP Programs
- Keyless Entry
- Keyless Lockers

Artwork Specifications:

Spot Color Specifications:

- CLEAN, BLACK AND WHITE LINE ART is required
- Tones and screens need to be converted to solids
- Broken lines, weak lines, or smeared art cannot be imprinted
- Outline all fonts in the artwork files



No tones or screens
(gray area)



No faxed art or
art with broken or
weak lines



Artwork must be clean,
black & white line art

| Preferred File Formats | | | |
|------------------------|-----------|--------------------------------------|--------------------------|
| Format | Extension | Description | Note |
| EPS | .eps | Illustrator encapsulated post script | Convert text to outlines |
| AI | .ai | Adobe Illustrator | Convert text to outlines |
| TIFF | .tif | Tagged image file format | 300-600 dpi or higher |
| JPG | .jpg | Joint Photographic Experts Group | 300-600 dpi or higher |

Note: If artwork is not supplied in the proper format and requires additional graphic design work, you may be billed for art charges.

No Logos / Artwork from a Website

We cannot use logos/artwork that are copied from a website as these images are low resolution and will produce a jagged, pixilated imprint with poor quality results.

E-Mail your Artwork

You may e-mail your artwork to artwork@pdc corp.com. Please include your company name, order number, contact name and phone number in your e-mail message.

Upload your Artwork Online

To upload your artwork through our website, go to www.pdcsolutions.com/artwork. Simply attach your artwork file.

Artwork Archives

We are happy to keep your wristband artwork on file for future re-orders. This will save you time and money. Please note, however, that if artwork is not used within a two year period, the archive artwork will be destroyed.

RFID Specifications:

| | NXP ICODE SLI | Texas Instruments Tag-It Plus | Mifare Standard 1K | UHF |
|----------------------------|---------------------------------|---------------------------------|----------------------------------|---|
| Operating Frequency | 13.56 MHz | 13.56 MHz | 13.56 MHz | 902-928 MHz |
| EEPROM Size | 128 byte (1024 bit) | 256 byte (2048 bit) | 1024 byte (8192 bit) | 64 byte (512 bit) User memory |
| Memory Organization | 32 blocks, 4 bytes per block | 64 blocks, 4 bytes per block | 16 sectors, 4 blocks of 16 bytes | 64 bit TID, 96 bit EPC, (512 bit) User |
| Unique Serial Number (UID) | 8 byte (64 bit) | 8 byte (64 bit) | 4 byte (32 bit) | 8 byte (64 bit) |
| RF Interface | ISO 15693-3 | ISO 15693-3 | ISO 14443A | ISO 18000-6C |
| Data Retention (years) | 10 | 10 | 10 | EPC Gen 2 |
| Write Endurance (cycles) | 100,000 | 100,000 | 100,000 | 10,000 |
| Read/Write Range | 3.5" / 8.9 cm | 3.5" / 8.9 cm | 1.5" / 3.8 cm | 5' / 152.4 cm |

North America & Latin America

U.S. Headquarters
27770 N. Entertainment Drive, Suite 200
Valencia, CA 91355
Tel: 866.403.6526
Tel: 661.257.0233 ext 1556
Fax: 818.686.9336
Email: rfid@pdcsolutions.com

Asia Pacific

Tel: +1.661.257.0233
Fax: +1.818.686.9317
Email: asia@pdcsolutions.com

Europe, Middle East & Africa

European Headquarters
Rue de l'Industrie, 17
1400 Nivelles, Belgium
Tel: +32 67 89 56 56
Fax: +32 67 21 77 70
Email: info@pdcsolutions.eu
Web: pdcsolutions.eu

